
KBS TEKNISK RAPPORT

75

**Small-scale bentonite injection test
on rock**

Roland Pusch

Högskolan i Luleå 1978-03-02

SMALL-SCALE BENTONITE INJECTION
TEST ON ROCK

Roland Pusch
Högskolan i Luleå 1978-03-02

Denna rapport utgör redovisning av ett arbete som utförts på uppdrag av KBS. Slutsatser och värderingar i rapporten är författarens och behöver inte nödvändigtvis sammanfalla med uppdragsgivarens.

I slutet av rapporten har bifogats en förteckning över av KBS hittills publicerade tekniska rapporter i denna serie.

TEKNISK RAPPORT **KBS 15**

REPORT ON

SMALL-SCALE BENTONITE INJECTION TEST ON ROCK

Luleå 1978-03-02

Div. Soil Mechanics, University of Luleå

R: PUSCH

SMALL-SCALE BENTONITE INJECTION TEST ON ROCK

Introduction

Irrespective of the kind of radioactive waste products which are going to be deposited, a sealing of the rock in which the deposition holes are located is very valuable since it reduces the rate of water percolation and diffusion.

There are a number of possible techniques which can be used to seal the rock. Injection of bentonite gels by means of over-pressure and subsequent electrophoresis ("electro-kinetic treatment") has been suggested earlier by the author (PUSCH, 1977) and preliminary tests with glass-plates instead of rock have been fairly successful.

The present report describes a rock test series where bentonite injection was applied.

The main idea was to simulate the real conditions in a tunnel at great depth (Fig.1a). For these conditions the main steps in the injection program are:

1. A central pilot hole and a series of fairly closely located outer holes are bored. The central hole is later enlarged to form the deposition hole (cf. Fig.1b).
2. The central pilot hole (or the final hole for deposition) is filled with a Na bentonite suspension (w = 1000-2000%).
3. An over-pressure is applied in the hole with the suspension (an under-pressure can be applied as well in the surrounding bore holes) by which the dilute bentonite gel is forced into joints which extend from the central hole.




Fig.1a. Schematic picture of tunnel and deposition hole (VBB).




Fig. 1b. Bore hole arrangement. Holes 3 are sealed by inserting fairly closely fitting cylindrical bodies of highly compacted bentonite.

4. Electrodes are installed in the holes (cathode in the central hole and anodes in the circumferential holes) and a 200-2000V direct current is applied for about a week. By this, additional clay particles are transported from the central hole into the joints. The clay particles belong to the montmorillonite mineral group which is the dominant constituent in bentonite.

Test arrangement

Rock type, block preparation

The limited capacity of the lifting device in the test hall (3 tons) implied a maximum block size of about 1 m³. The block, which had an approximately cubical shape, was selected from a road construction work in Luleå on the 3rd of January. The rock type was diorite (metabasite) with a fairly high frequency of quartz lenses. The site from where the block was taken was located below the ground water level. Since the air temperature was well below -10°C the water in the joints froze and preserved the state of water saturation. In the warm test hall the block was flooded and covered to maintain this state (Fig. 2).

After core drilling it was transferred to a basin where it was submerged during the tests. To prevent permanent opening of joints by the pressure injection operations and to simulate the lateral support of the tunnel base, the block was confined in 15 cm reinforced concrete except for the upper side with the bore holes (Fig. 3).




Fig. 2. Drilling device. The block was covered with plastic sheets to maintain water saturation.




Fig. 3. Top surface of the concrete-confined block with electrodes installed. Pipe connections of glass and plastic were used for permeability measurement.

The holes, which were placed according to Fig. 4, were 4.3 cm in diameter and 48 cm deep. Holes no.1, 5 and 6 had to be inclined somewhat towards the central hole because of the irregular external shape of the block. No direct connection between the holes through joints or fissures could be seen with the naked eye. The regular joint pattern shown in Fig. 4 can be seen in the photograph in Fig. 3 also.




Fig. 4. Schematic top view of the block.

The cores (Fig. 5) were inspected with reference to joints and fissures, the observations being listed in Table 1.





Fig. 5. Cores with joints indicated by arrows. Note that cores from hole 4 and 7 show no joints or fissures. The rather fine-grained rock matrix is rich in biotite and hornblende. As seen in the picture quartz lenses and laminae are frequent.

Table 1. Observed openings in cores. (Cores 4 and 7 dense).

	1	2	3	5	6
0					
5	Steep joint				
10				Slightly incl. joint	Slightly incl. joint
15	Horiz. joint		Incl. joint in quartz		Steep joint
20					
25		Horiz. joint		Axial joint	Horiz. joint
30					
35		Joint system	Joint system		
40				Joint system	Joint system
45					
50					

It should be noticed that the cores from the "deposition hole" (no. 7) and hole no. 4 had no joints or fissures. They gave the impression of being perfectly free from any kind of openings. It was not possible to draw any conclusions from the core inspection as concerns possible connections between the various holes. However, the permeability tests and the disintegration of the block after the test gave the information collected in Fig. 6. It is concluded that there is a connection through horizontal or slightly inclined joints between holes 1, 2, 5, 6 and (the base of) hole 7. The width of one joint was about 0.4 mm but most of them were probably less than 0.1 mm wide. The pore volume of the block estimated from the detailed determina-



A connects 5, 6 and
 (base of) 1, 2 and 7.
 B connects 1, 5 and 6.

CDEA connects 3 and 7.

Fig. 6. Main joints.





Fig. 7. Electrode.
Upper picture: Schematic drawing. Lower picture: Dismantled and mounted electrodes.

tion of the width and extension of the joints and from the injection work was about 500 ml. This means that the average porosity was about $5 \cdot 10^{-4}$.

In order to make possible both the over-pressure and the "electro-kinetic" injection as well as the permeability tests, electrodes of the type shown in Fig. 7 were mounted in the holes. Greased rubber O-rings were used for sealing purposes.

Some preliminary short-term pilot tests were used to find out the most suitable percolation technique and to test whether compressed air could be used for injection purposes. In order to restore the block after these pilot tests the holes and joints had to be washed by water under 500 kPa pressure before the main test started. This may have created some permanent joint opening.

Test program

The following program was chosen:

1. Percolation test of each individual hole (only one test at the time) using the falling head principle and starting with 1 m head (10 kPa water pressure at the upper end of each hole).¹⁾
2. Injection of a bentonite slurry with 100% water content (2% NaCl solution) by means of a specially designed, easily operated injection pump (Fig. 8). The pump house was filled with the slurry which was injected

¹⁾ Here, the preliminary tests came in by which some increase of the joint width may have been caused.

under a constant pressure of 1 MPa. After the injection of 350 ml, which took about 2 hours, the operation was stopped. A minor extrusion of water and bentonite suspension was observed along line I-I in Fig. 4 which indicates the presence of an irregular joint with connection to hole no. 7.




Fig. 8. Injection pump in operation.

3. Percolation test as in Paragraph 1 after thorough cleaning of the "deposition hole" no. 7. Samples of the water in holes no. 1-6 were first taken to find out whether montmorillonite had been transferred from hole no. 7.
4. Electro-kinetic treatment. The central, deposition hole was again filled with a 1000% water content (2% NaCl solution) bentonite slurry to which a small amount of a

gold sol was added. This substance formed positively charged particles of colloidal size which were thus adsorbed on negatively charged basal planes of montmorillonite particles. The intention was to mark the montmorillonite so that particles transferred by the electrical field from the central hole to the peripheral holes and transported out into joints could be identified by applying electron microscopy.

A 240 volt potential was then applied for 4 days, the electrode in the deposition hole (no.7) being cathode and all the other electrodes being anodes. The current decreased from 16-40 mA to 3-10 mA at the end of the treatment. It was initially about 35-40 mA for holes no. 1, 2, 5 and 6 while it was only about 16 mA for holes no. 3 and 4. This indicates a different degree of connection between the circumferential holes and the central hole. Thus, holes no. 3 and 4 seem to have little or no connection with hole no.7.

5. Percolation test as in Paragraph 1 after thorough cleaning of the deposition hole.
6. The block was split to expose the joints and to investigate them with reference to width and orientation and to their content of montmorillonite.

Test results

Permeability

Ground water flow in rock takes place in continuous joints (rapid flow) and in continuous pore systems



(mainly incomplete grain contacts; slow flow) as shown by PUSCH, 1977. The large majority of the water flow takes place in one or two joints per unit volume and it is therefore hardly relevant to describe the circulation pattern by using flow nets for an assumed isotropic medium or by applying the term (average) permeability.

This was also obvious from some preliminary permeability tests which indicated a very complex joint pattern. They showed that the best way of describing the time-dependent clearance of the holes was to measure the time for clearance of each individual hole when the water level outside the block and within all the holes (except the one being tested) and all joints was the same (cf. Test program). It is true that this does not give any information as to where the water flows which means that the length of the water passage and, thus, the hydraulic gradient are not known. The coefficient of permeability can therefore not be used. For the present purpose the main thing was to find out the percolation rate before and after the various treatments. In the report, therefore, this rate is simply given in terms of the time required to dissipate 50 ml of water from each hole in a "falling head" test with 1 m head at the start of each test. A very rough estimate gives the value 2.0 for the hydraulic gradient at the test start.

The results of the percolation tests are given in Fig. 9, 10 and 11. They are commented as follows:



Hole no 1
.....

The time for clearance of this hole before the treatments was about 12 minutes. The pressure-injected bentonite doubled this time. The most effective sealing was obviously produced by the electro-kinetic treatment by which the time was increased to 9 hours.





- Before treatment
 - - - - - After pressure-injection
 - - - - - After electro-kinetic treatment

Fig. 9. Percolation tests. Upper picture: Hole no 1.
Lower picture: Hole no 2.



- · — · — Before treatment
- After pressure-injection
- After electro-kinetic treatment

Fig. 10. Percolation tests. Upper picture: Hole no 3.
Lower picture: Hole no 5.



- Before treatment
- After pressure-injection
- After electro-kinetic treatment

Fig. 11. Percolation tests. Upper picture: Hole no 6.
Lower picture: Hole no 7.

Hole no 2

As in hole no 1 only the electro-kinetic treatment was really effective. It is obvious, however, that also after this treatment fairly large water passages extend from the hole. This is explained by Fig. 5 which shows a very open joint system at the lower third of the core. A largely prolonged electrical treatment should have improved the sealing.

Hole no 3

Same comment as for hole no. 2. The rather small effect is also due to the tortuous passage-way from hole no. 7.

Hole no 4

No water loss before or after the treatments could be observed.

Hole no 5

The bentonite injections were not especially successful. Again this is probably due to fairly large openings (cf. Fig. 5).

Hole no 6

We get the impression that the injections reduce the time for clearance in this test. As mentioned previously the preliminary tests with compressed air etc probably opened the frequent joints (cf. Fig. 5). Also, the injection of the bentonite gel by means of the injection pump may have caused an additional widening. This hole was situated close to the block surface so the pressure-injection may in fact have produced a local splitting of the rock and concrete.

Hole 7
.....

This hole is the most interesting since it represents the deposition hole where the injections were performed. We see that the pressure-injection contributed considerably to the sealing of the rock (the test had to be finished after 27 hours) but that the electro-kinetic treatment was the most effective one.

We can conclude from these measurements that a pressure-injection in a bore hole from a tunnel floor should be much more effective than our test since the confining rock is pre-stressed and gives a very effective lateral support with less risk of joint opening. This requires, however, that no tensile stresses exist in the confining rock.

We also find that the electro-kinetic treatment works and that it gives a valuable contribution to the sealing. Very probably a more efficient technique can be developed, for instance by applying other potentials and by making a series of prolonged electrical treatments with pressure-injections in between.

It is interesting to see that while the pressure-injection transferred 350 ml bentonite suspension out into the joints (that is about 35 g of solid clay), the electrical treatment brought an additional amount of 15 g of solid clay out into these joints. The effect of the electrical treatment was of course also that of transporting pressure-injected clay further out into the joints. This is probably the major effect of this treatment.

It should be mentioned that the physical process which transfers minute negatively charged clay particles towards the positive anodes is accompanied by an electro-osmotic water transport towards the

cathode in the central hole. This was manifested by a slow rise of water in the standpipe of the cathode. The water column had risen to about 25 cm above the external water level when the test was stopped.

The transfer of clay

The splitting of the block (cf. Fig. 12) showed that the main joints in Fig. 6 contained a thin film of fairly stiff montmorillonite gel.




Fig. 12. Block splitting operation

The stiffness of the clay was much higher than that of gelled bentonite suspensions with a water content of 1000%. This means that consolidation occurred in course of the pressure-injection and/or that electro-phoresis increased the concentration of the gel. The latter process was observed in the previous glass-plate tests (PUSCH, 1977) and must

have contributed to the increased density.

Four representative samples were taken from various joints for mineral identification. The positions were (cf. Fig. 6): 1) Joint A between bore holes no. 1 and 2, 2) Joint B between bore holes no. 1 and 7 (passage way from base of hole no. 7 via joint A through hole no. 1 into joint B), 3) Joint B close to hole 5 (passage way from base of hole no. 7 via joint A through hole no. 5 into joint B, 4) Crossing of joints F and G 8 cm from top surface (passage way from base of hole no. 7 via joint A through joints F and G.

All the samples showed the presence of biotite and montmorillonite. The biotite originates from the rock while the montmorillonite is an evidence of the successful injection operations. This is because the rock is completely free from the natural weathering products. Fig. 13 is an example of the X-ray diffraction pattern for the sample from location 4. The conclusion of this study is that montmorillonite has been able to move a considerable distance despite the very tortuous passage-ways. This is most certainly an effect of the electro-kinetical treatment.

The water samples taken in the outer bore holes before and after the pressure-injection were investigated by means of electron microscopy. Due to the large amount of cations (the electrodes are dissolved as a result of the electrical treatment) and the low pH the montmorillonite flocculated immediately and settled to the base of the bore holes where it was mixed with rock flour. The electron micrographs are therefore difficult to interpret. Very probably, however, the frequently occurring extremely small and thin flakes represent this mineral (Fig. 14).




Fig. 13. X-ray diffraction pattern for sample from joint (no. 4). EG indicated the position to which the montmorillonite peak shifts after ethylene glycol treatment.




Fig. 14. Electron micrographs of samples from the bentonite slurry in bore hole 7 (for comparison) and from bore hole 3. The mineral assembly in the lower picture contains a number of small and very thin flakes.

Unfortunately, the colloidal gold particles could not be identified with certainty (cf. PUSCH, 1962 for technique description). It should be added that the montmorillonite in bore hole no. 3 had passed through such a tortuous joint system that the electrical field must have been the driving force.

Conclusions

The main conclusions from this investigation are:

- ★ Pressure-injection of dilute bentonite suspensions ($w \sim 1000$) has a sealing effect but the depth of extrusion of the suspension into rock joints is probably not large because of gelation of the strongly thixotropic substance.
- ★ Electro-kinetic injection of montmorillonite particles from a Na bentonite gel is a promising technique for rock tightening. It was found to be more effective than the pressure-injection. This was probably due to the electro-phoretic particle transport far out into the joints, directly from the central hole through the pressure-injected bentonite, and from the outer part of this bentonite.
- ★ Since the clay particles have a net negative electrical charge they are transported towards the anodes, which should therefore be arranged around the central hole with the cathode. In practice, the joint system of the rock mass is not known in detail when the location of the bore holes with anodes is to be decided. This is of no importance since the electrical field is con-

tinuous and transports clay particles towards the anodes in any kind of passages, provided that they begin at the deposition hole or are connected with joints which start there. A further testing of the technique on a larger scale should now be made.

References

- PUSCH, R, 1962 Clay Particles, then size, shape and arrangement in relation to some important physical properties of clays. BFR, Handlingar nr 40.
- PUSCH, R, 1977 Bergspricktätning med bentonit. KBS Teknisk Rapport (Teknisk Rapport 10 in LuH's series).

FÖRTECKNING ÖVER KBS TEKNISKA RAPPORTER

- 01 Källstyrkor i utbränt bränsle och högaktivt avfall från en PWR beräknade med ORIGEN
Nils Kjellbert
AB Atomenergi 77-04-05
- 02 PM angående värmeledningstal hos jordmaterial
Sven Knutsson
Roland Pusch
Högskolan i Luleå 77-04-15
- 03 Deponering av högaktivt avfall i borrhål med buffertsubstans
Arvid Jacobsson
Roland Pusch
Högskolan i Luleå 77-05-27
- 04 Deponering av högaktivt avfall i tunnlar med buffertsubstans
Arvid Jacobsson
Roland Pusch
Högskolan i Luleå 77-06-01
- 05 Orienterande temperaturberäkningar för slutförvaring i berg av radioaktivt avfall, Rapport 1
Roland Blomqvist
AB Atomenergi 77-03-17
- 06 Groundwater movements around a repository, Phase 1, State of the art and detailed study plan
Ulf Lindblom
Hagconsult AB 77-02-28
- 07 Resteffekt studier för KBS
Del 1 Litteraturgenomgång
Del 2 Beräkningar
Kim Ekberg
Nils Kjellbert
Göran Olsson
AB Atomenergi 77-04-19
- 08 Utlakning av franskt, engelskt och kanadensiskt glas med högaktivt avfall
Göran Blomqvist
AB Atomenergi 77-05-20

- 09 Diffusion of soluble materials in a fluid filling a porous medium
Hans Häggblom
AB Atomenergi 77-03-24
- 10 Translation and development of the BNWL-Geosphere Model
Bertil Grundfelt
Kemakta Konsult AB 77-02-05
- 11 Utredning rörande titans lämplighet som korrosionshärdig kapsling för kärnbränsleavfall
Sture Henriksson
AB Atomenergi 77-04-18
- 12 Bedömning av egenskaper och funktion hos betong i samband med slutlig förvaring av kärnbränsleavfall i berg
Sven G Bergström
Göran Fagerlund
Lars Rombén
Cement- och Betonginstitutet 77-06-22
- 13 Urlakning av använt kärnbränsle (bestrålad uranoxid) vid direktdeponering
Ragnar Gelin
AB Atomenergi 77-06-08
- 14 Influence of cementation on the deformation properties of bentonite/quartz buffer substance
Roland Pusch
Högskolan i Luleå 77-06-20
- 15 Orienterande temperaturberäkningar för slutförvaring i berg av radioaktivt avfall
Rapport 2
Roland Blomquist
AB Atomenergi 77-05-17
- 16 Översikt av utländska riskanalyser samt planer och projekt rörande slutförvaring
Åke Hultgren
AB Atomenergi augusti 1977
- 17 The gravity field in Fennoscandia and postglacial crustal movements
Arne Bjerhammar
Stockholm augusti 1977
- 18 Rörelser och instabilitet i den svenska berggrunden
Nils-Axel Mörner
Stockholms Universitet augusti 1977
- 19 Studier av neotektonisk aktivitet i mellersta och norra Sverige, flygbildsgenomgång och geofysisk tolkning av recenta förkastningar
Robert Lagerbäck
Herbert Henkel
Sveriges Geologiska Undersökning september 1977

- 20 Tektonisk analys av södra Sverige, Vättern - Norra Skåne
Kennert Röshoff
Erik Lagerlund
Lunds Universitet och Högskolan Luleå september 1977
- 21 Earthquakes of Sweden 1891 - 1957, 1963 - 1972
Ota Kulhánek
Rutger Wahlström
Uppsala Universitet september 1977
- 22 The influence of rock movement on the stress/strain
situation in tunnels or bore holes with radioactive con-
sistors embedded in a bentonite/quartz buffer mass
Roland Pusch
Högskolan i Luleå 1977-08-22
- 23 Water uptake in a bentonite buffer mass
A model study
Roland Pusch
Högskolan i Luleå 1977-08-22
- 24 Beräkning av utlakning av vissa fissionsprodukter och akti-
nider från en cylinder av franskt glas
Göran Blomqvist
AB Atomenergi 1977-07-27
- 25 Blekinge kustgnejs, Geologi och hydrogeologi
Ingemar Larsson KTH
Tom Lundgren SGI
Ulf Wiklander SGU
Stockholm, augusti 1977
- 26 Bedömning av risken för fördröjt brott i titan
Kjell Pettersson
AB Atomenergi 1977-08-25
- 27 A short review of the formation, stability and cementing
properties of natural zeolites
Arvid Jacobsson
Högskolan i Luleå 1977-10-03
- 28 Värmeledningsförsök på buffertsubstans av bentonit/pitesilt
Sven Knutsson
Högskolan i Luleå 1977-09-20
- 29 Deformationer i sprickigt berg
Ove Stephansson
Högskolan i Luleå 1977-09-28
- 30 Retardation of escaping nuclides from a final depository
Ivars Neretnieks
Kungliga Tekniska Högskolan Stockholm 1977-09-14
- 31 Bedömning av korrosionsbeständigheten hos material avsedda
för kapsling av kärnbränsleavfall. Lägesrapport 1977-09-27
samt kompletterande yttranden.
Korrosionsinstitutet och dess referensgrupp

- 32 Long term mineralogical properties of bentonite/quartz
buffer substance
Preliminär rapport november 1977
Slutrapport februari 1978
Roland Pusch
Arvid Jacobsson
Högskolan i Luleå
- 33 Required physical and mechanical properties of buffer masses
Roland Pusch
Högskolan Luleå 1977-10-19
- 34 Tillverkning av bly-titan kapsel
Folke Sandelin AB
VBB
ASEA-Kabel
Institutet för metallforskning
Stockholm november 1977
- 35 Project for the handling and storage of vitrified high-level
waste
Saint Gobain Techniques Nouvelles October, 1977
- 36 Sammansättning av grundvatten på större djup i granitisk
berggrund
Jan Rennerfelt
Orrje & Co, Stockholm 1977-11-07
- 37 Hantering av buffertmaterial av bentonit och kvarts
Hans Fagerström, VBB
Björn Lundahl, Stabilator
Stockholm oktober 1977
- 38 Utformning av bergrumsanläggningar
Arne Finné, KBS
Alf Engelbrektson, VBB
Stockholm december 1977
- 39 Konstruktionsstudier, direktdeponering
ASEA-ATOM
VBB
Västerås
- 40 Ekologisk transport och stråldoser från grundvattenburna
radioaktiva ämnen
Ronny Bergman
Ulla Bergström
Sverker Evans
AB Atomenergi
- 41 Säkerhet och strålskydd inom kärnkraftområdet.
Lagar, normer och bedömningsgrunder
Christina Gyllander
Siegfried F Johnson
Stig Rolandson
AB Atomenergi och ASEA-ATOM

- 42 Säkerhet vid hantering, lagring och transport av använt kärnbränsle och förglasat högaktivt avfall
Ann Margret Ericsson
Kemakta november 1977
- 43 Transport av radioaktiva ämnen med grundvatten från ett bergförvar
Bertil Grundfelt
Kemakta november 1977
- 44 Beständighet hos borsilikatglas
Tibor Lakatos
Glasteknisk Utveckling AB
- 45 Beräkning av temperaturer i ett envånings slutförvar i berg för förglasat radioaktivt avfall Rapport 3
Roland Blomquist
AB Atomenergi 1977-10-19
- 46 Temperaturberäkningar för använt bränsle
Taivo Tarandi
VBB
- 47 Teoretiska studier av grundvattenrörelser
Preliminär rapport oktober 1977
Slutrapport februari 1978
Lars Y Nilsson
John Stokes
Roger Thunvik
Inst för kulturteknik KTH
- 48 The mechanical properties of the rocks in Stripa, Kråkemåla, Finnsjön and Blekinge
Graham Swan
Högskolan i Luleå 1977-09-14
- 49 Bergspänningsmätningar i Stripa gruva
Hans Carlsson
Högskolan i Luleå 1977-08-29
- 50 Läckningsförsök med högaktivt franskt glas i Studsvik
Göran Blomqvist
AB Atomenergi november 1977
- 51 Seismotectonic risk modelling for nuclear waste disposal in the Swedish bedrock
F Ringdal
H Gjøystdal
E S Hysebye
Royal Norwegian Council for scientific and industrial research
- 52 Calculations of nuclide migration in rock and porous media, penetrated by water
H Häggblom
AB Atomenergi 1977-09-14

- 53 Mätning av diffusionshastighet för silver i lera-sand-blandning
Bert Allard
Heino Kipatsi
Chalmers tekniska högskola 1977-10-15
- 54 Groundwater movements around a repository
- 54:01 Geological and geotechnical conditions
Håkan Stille
Anthony Burgess
Ulf E Lindblom
Hagconsult AB september 1977
- 54:02 Thermal analyses
Part 1 Conduction heat transfer
Part 2 Advective heat transfer
Joe L Ratigan
Hagconsult AB september 1977
- 54:03 Regional groundwater flow analyses
Part 1 Initial conditions
Part 2 Long term residual conditions
Anthony Burgess
Hagconsult AB oktober 1977
- 54:04 Rock mechanics analyses
Joe L Ratigan
Hagconsult AB september 1977
- 54:05 Repository domain groundwater flow analyses
Part 1 Permeability perturbations
Part 2 Inflow to repository
Part 3 Thermally induced flow
Joe L Ratigan
Anthony S Burgess
Edward L Skiba
Robin Charlwood
- 54:06 Final report
Ulf Lindblom et al
Hagconsult AB oktober 1977
- 55 Sorption av långlivade radionuklider i lera och berg
Del 1 Bestämning av fördelningskoefficienter
Del 2 Litteraturgenomgång
Bert Allard
Heino Kipatsi
Jan Rydberg
Chalmers tekniska högskola 1977-10-10
- 56 Radiolys av utfyllnadsmaterial
Bert Allard
Heino Kipatsi
Jan Rydberg
Chalmers tekniska högskola 1977-10-15

- 57 Stråldoser vid haveri under sjötransport av kärnbränsle
Anders Appelgren
Ulla Bergström
Lennart Devell
AB Atomenergi 1978-01-09
- 58 Strålrisker och högsta tillåtliga stråldoser för människan
Gunnar Walinder
FOA 4 november 1977
- 59 Tectonic lineaments in the Baltic from Gävle to Simrishamn
Tom Flodén
Stockholms Universitet 1977-12-15
- 60 Förarbeten för platsval, berggrundsundersökningar
Sören Scherman
- Berggrundvattenförhållande i Finnsjöområdet nordöstra del
Carl-Erik Klockars
Ove Persson
Sveriges Geologiska Undersökning januari 1978
- 61 Permeabilitetsbestämningar
Anders Hult
Gunnar Gidlund
Ulf Thoregren
- Geofysisk borrhålmätning
Kurt-Åke Magnusson
Oscar Duran
Sveriges Geologiska Undersökning januari 1978
- 62 Analyser och åldersbestämningar av grundvatten på stora djup
Gunnar Gidlund
Sveriges Geologiska Undersökning 1978-02-14
- 63 Geologisk och hydrogeologisk grunddokumentation av
Stripa försöksstation
Andrei Olkiewicz
Kenth Hansson
Karl-Erik Almén
Gunnar Gidlund
Sveriges Geologiska Undersökning februari 1978
- 64 Spänningsmätningar i Skandinavisk berggrund - förutsättningar,
resultat och tolkning
Sten G A Bergman
Stockholm november 1977
- 65 Säkerhetsanalys av inkapslingsprocesser
Göran Carleson
AB Atomenergi 1978-01-27
- 66 Några synpunkter på mekanisk säkerhet hos kapsel för
kärnbränsleavfall
Fred Nilsson
Kungl Tekniska Högskolan Stockholm februari 1978

- 67 Mätning av galvanisk korrosion mellan titan och bly samt mätning av titans korrosionspotential under γ - bestrålning.
3 st tekniska PM.
Sture Henrikson
Stefan Poturaj
Maths Åsberg
Derek Lewis
AB Atomenergi januari-februari 1978
- 68 Degraderingsmekanismer vid bassänlagring och hantering av utbränt kraftreaktorbränsle
Gunnar Vesterlund
Torsten Olsson
ASEA-ATOM 1978-01-18
- 69 A three-dimensional method for calculating the hydraulic gradient in porous and cracked media
Hans Häggblom
AB Atomenergi 1978-01-26
- 70 Lakning av bestrålat UO_2 -bränsle
Ulla-Britt Eklund
Ronald Forsyth
AB Atomenergi 1978-02-24
- 71 Bergspricktätning med bentonit
Roland Pusch
Högskolan i Luleå 1977-11-16
- 72 Värmeledningsförsök på buffertsubstans av kompakterad bentonit
Sven Knutsson
Högskolan i Luleå 1977-11-18
- 73 Self-injection of highly compacted bentonite into rock joints
Roland Pusch
Högskolan i Luleå 1978-02-25
- 74 Highly compacted Na bentonite as buffer substance
Roland Pusch
Högskolan i Luleå 1978-02-25
- 75 Small-scale bentonite injection test on rock
Roland Pusch
Högskolan i Luleå 1978-03-02
- 76 Experimental determination of the stress/strain situation in a sheared tunnel model with canister
Roland Pusch
Högskolan i Luleå 1978-03-02
- 77 Nuklidvandring från ett bergförvar för utbränt bränsle
Bertil Grundfelt
Kemakta konsult AB, Stockholm
- 78 Bedömning av radiolys i grundvatten
Hilbert Christenssen
AB Atomenergi 1978-02-17